



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 083-001
Product name **Web Type Spray Adhesive**
Effective date 18-Nov-2010
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 1-630-628-3000
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 05
Supersedes date 04-Mar-2009

2. Hazards Identification

Emergency overview Aerosol. EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. Will be easily ignited by heat, spark or flames.

Potential health effects

Eyes Health injuries are not known or expected under normal use.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

Signs and symptoms Discomfort in the chest. Narcosis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Propane	74-98-6	20 - 30
n-Butane	106-97-8	20 - 30
Heptane	142-82-5	15 - 20
Acetone	67-64-1	15 - 20
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water.
Protection of firefighters	
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.
Methods for cleaning up	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Heptane	142-82-5	400 ppm	500 ppm	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Heptane	142-82-5	500 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Not normally needed.
Skin protection	Wear appropriate chemical resistant gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	46.4 °F (7.8 °C) estimated
Color	clear amber

Density	0.6413 g/cm ³ estimated
Flammability (HOC)	41.85 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) estimated
Form	Liquid. Aerosol.
Freezing point	Not available
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	65 - 85 psig @ 70F
Solubility	Partially
Specific gravity	0.6414

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LC50: 323 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
Heptane	142-82-5	Inhalation LC50 Rat 103 g/m ³ 4 h; Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Teratogenicity Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 1794 mg/L estimated, Fish, 96.00 Hours, EC50 78756 mg/L estimated, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions Contents under pressure. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None

Additional information:

Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Item 5F
Labels required None
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance No
Section 311 hazardous chemical Yes
Hazard categories (311/312) Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Chemical	Inventory Number	Inventory Status
Acetone	67-64-1	Environmental hazard
Heptane	142-82-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information

HMIS Trademark Statement

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Product and Company Identification: Product Review
Transport Information: Product Shipping Name/Packing Group
Regulatory Information: United States

Prepared by

Regulatory Compliance